

北方爆破工程有限责任公司

山西省阳泉市十南大街 271 号

导爆索 DETONATING CORD

Technical Data Sheet

第一部分 化学品名称

<p>商品中文名称：导爆索</p> <p>商品英文名称 Commercial Name: Detonating Cord</p> <p>联合国编号 UN Nr.: 0065</p> <p>危险性类别 Hazard Code: 第 1 类第 1.1D 项爆炸品</p> <p>保质期 Shelf Life : 5 年</p> <p>生产和验收执行: GB/T8946-1998, GB11115-1989</p>	
<p>企业名称：北方爆破工程有限责任公司</p> <p>地址：山西省阳泉市十南大街 271 号</p> <p>邮编：</p> <p>传真号码：</p> <p>企业应急电话：</p>	

第二部分 产品简介和描述

<p>导爆索以 PETN 为药芯，用纤维等为包缠物，外层涂覆热塑性塑料。用于石油、煤炭等矿藏的勘探，也可用于采石爆破，适用于一般无沼气、煤尘爆炸危险的工程爆破。</p>
--

第三部分 成分/组成信息 成分构成如下：

规格 (克)	组分名称 / 组分含量				
	PETN g / m	聚丙烯条 g / m	高压聚乙烯 g / m	约净重 g / m	每箱数量 m
5	6.0±0.5	3.2	4.2	13.4	1000
11	≥10.5	4.2	5.2	20.4	800
40	38±2	7.8	8.1	53.9	200
备注	*可按客户要求调整				

北方爆破工程有限责任公司

山西省阳泉市十南大街 271 号

DETONATING CORD

Brief Introduction:

It is a blasting accessory for transmitting detonation wave. It consists of an explosive core and moisture resistant jacket, primarily used for initiating explosives and also for metal cutting, explosion formation and explosion bonding.

Specifications:

Type	3.6 g/m	5 g/m	6 g/m	8 g/m	10 g/m	11 g/m	12 g/m	14 g/m	40 g/m
Diameter (mm)	≤3.8	3.8-4.2	3.8-4.2	4.4-4.6	4.6-5.0	4.8-5.2	4.8-5.2	5.6-6.0	≤9.5
Tensile strength (kg), ≥	80						100	100	
Reel length (m)	50							100	100
Explosive velocity (m/s), ≥	6500								
Temperature range(°C)	-40~75								
Water resistance	Retain sensitivity after being exposed to immersion in static water, ambient temperature and under the pressure of 50 Kpa for 5 hours								
Wrap materials	Plastic or cotton yarn								


Remark: The color and the length of coil can be adjusted according to client's request.

Shelf life: 5 years

Packing: 200-1000 meter per carton

UN Classification Class: 1.1D

UN. No: 0065



BEIJING AUXIN CHEMICAL TECHNOLOGY LTD.