

Shock*Star Surface

PRODUCT INFORMATION BROCHURE

SHOCK*STAR SURFACE connectors are especially designed for the initiation of other shock tube detonators and to introduce a delay between holes.

The connector block is designed to ensure reliable connections in two positions:

- unlocked position for normal working conditions
- locked position for most demanding working conditions with a risk of disconnection (e.g. under heavy mats).

SHOCK*STAR SURFACE connectors are equipped with connector blocks able to contain 8 outgoing shock tubes. The connectors have a lowered base charge to reduce noise levels and eliminate shrapnel cut-off concerns.

SHOCK*STAR SURFACE detonator can also be used for blast initiation. It is produced in lengths of 150, 300, 500 and 750 m and is supplied on spools. SHOCK*STAR SURFACE connectors must not be used for initiation of detonating cord.



BENEFITS

- Easy shock tube connection, Locking mechanism to ensure locking of the tubes in the block if needed. Capacity of 8 shock tubes.
- Colour coding according to the delay time of the detonator.
- Excellent delay time accuracy ensures greater than 99% probability of in-sequence initiation.
- Manufactured with red shock tubing for easy differentiation from in-hole detonators when inspecting the connected blast pattern.
- High impact protection.

PROPERTIES

Range of delays consists of 5 delay periods.



17 ms 25 ms 42 ms 67 ms 100 ms



AUSTIN POWDER

Tenaga Kimia-Austin Detonator Sdn. Bhd. (580221-P)
(formerly known as Tenaga Kimia-Ensign Bickford Sdn Bhd)

No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan. Tel : 603 - 7729 7464 | Fax : 603 - 7729 8383

Shock*Star Surface

PRODUCT INFORMATION BROCHURE

STANDARD TECHNICAL DESCRIPTION

DETONATOR	
Detonator shell material	Aluminum
Base charge	120 mg
Water pressure resistivity	0.3 MPa / 7 days
Temperature range for application	from -30 °C to +60 °C
Shelf life (storage conditions)	2 years (-30 °C to +40 °C, R.H. max. 65%) in original, sealed package
Label marking	Delay #, Detonator type, Delay ms, ST length, Order number
SHOCK TUBE	
Velocity of detonation	2,000 ± 100 m/s
Color	Red

STANDARD PACKAGING DETAILS

Shock tube length (m)	Packaging 1.4S UN 0500
	Units / Box
2.4	120
3.6	100
4.8	90
6.0	80
7.2	70
9	60
12	45
15	35
24	25

SHOCK*STAR SURFACE detonators are packaged in cardboard carton of outer dimension 385x235x282 mm.

*SPOOLS ON DEMAND.

(Only applicable for purchases 30 meters and above)*

Contact your local Austin Powder representative for further information.

Disclaimer of Warranties and Limitations of Liabilities

The data set forth in this Product Information Brochure (PIB) are based on the product test procedures of Tenaga Kimia-Austin Detonator Sdn Bhd in use at the time of publication of this PIB. Specifications, test values and information are exclusively non-binding preliminary information and are not guaranteed; the actual data may differ for various reasons (e.g. temperature, humidity, pressure). Technical inaccuracies or typographical errors and the right to amend the PIB at any time without notice shall be reserved. Tenaga Kimia-Austin Detonator Sdn Bhd, its subsidiaries and distributors do not assume any liability, covenants, guaranties or warranties with respect to the completeness, accuracy, reliability, suitability or availability of the product and the information of the PIB.

Any liability for damages of any kind (such as direct or indirect, incidental or consequential damages, losses or expenses), directly or indirectly related for any reason to this PIB or the use of the products is excluded. The customer is (even when making decisions based on the information in the PIB) solely responsible for the proper use of the potentially dangerous products that, accordingly, may only be used by trained personnel and in compliance with applicable law. To the entire legal relationship between their customers and Tenaga Kimia-Austin Detonator Sdn Bhd their (TKAD) general terms and conditions (please refer to standard terms of sale) shall apply.



AUSTIN POWDER

Tenaga Kimia-Austin Detonator Sdn. Bhd. (580221-P)
(formerly known as Tenaga Kimia-Ensign Bickford Sdn Bhd)

No. 8, Jalan SS 22/21, Damansara Jaya, 47400 Petaling Jaya, Selangor Darul Ehsan. Tel : 603 - 7729 7464 | Fax : 603 - 7729 8383



01/2019